



Regular Wire Rope Splicing Grips

Part Number	Cable Diameter	Approx. Breaking Strength In LBS	Approx. Strength of Grip In Feet
#03316001	9/16"-5/8"	7,500	5.75
#03316002	3/4"-7/8"	12,500	6.75
#03316003	1"-1-1/8"	16,000	7
#03316004	1-1/4"-1-3/8"	20,000	8
#03316006	1-3/8"-1-1/2"	20,000	8



Rotating Wire Rope Splicing Grips

Part Number	Cable Diameter	Approx. Breaking Strength In LBS	Approx. Strength of Grip In Feet	Barrel Dimensions Length x O.D.
#03317001	7/16"-1/2"	5,000	5.33	3.00" x 0.87"
#03317002	9/16"-5/8"	7,500	5.83	4.25" x 1.00"
#03317003	3/4"-7/8"	12,500	6.5	4.25" x 1.00"
#03317004	1"-1-1/8"	16,000	8.67	5.50" x 1.37"
#03317005	1-1/4"-1-3/8"	20,000	9	5.50" x 1.37"
#03317006	1-1/2"-1-3/4"	20,000	11	5.50" x 1.37"

Wire Rope Grips are made of high strength galvanized steel strand in a construction of triple, double and single weave for superior gripping ability. They are available with or without a rotating barrel which will help eliminate twist in the old rope from being transferred to the new rope.